

JOB NAME _____
 ARCHITECT _____
 ENGINEER _____
 CONTRACTOR _____
 LOCATION _____

SUBMITTAL SHEET
 Form Number GS0003.7 Effective Date 3/16
 Replaces Form GS0003.6



S80P SERIES Perforated Return

S80P FR 22 w/OBD

PERF DETAIL

S80P FRAME 22 – FACE VIEW

S80P FR 22

BASIC FASTENING METHODS

NO SCREW HOLES

STANDARD SCREW HOLES

S80P FR 23 w/OBD

FRAME 23

MAXIMUM DUCT SIZE EQUALS PANEL SIZE LESS 5" (127)

1" FILTER FRAME 2 3/8" (62)

2" FILTER FRAME 3 5/8" (93)

PANEL SIZE LESS 1/4" (6)

GRILLE FRAME

5/16" (8)

S80P FRAME 23 - FACE VIEW

S80P FR 23

S80P FR 98 w/OBD

FRAME 98

MAXIMUM DUCT SIZE EQUALS PANEL SIZE LESS 5" (127)

1" FILTER FRAME 2 3/8" (62)

2" FILTER FRAME 3 5/8" (93)

PANEL SIZE LESS 1/4" (6)

GRILLE FRAME

5/16" (8)

S80P FRAME 98 - FACE VIEW

S80P FR 98

FRAME 22

DUCT SIZE

1" FILTER FRAME 2 3/8" (62)

2" FILTER FRAME 3 5/8" (93)

DUCT PLUS 3 3/4" (96)

KNURLED / HINGE TOP

KNURLED / HINGE BOTTOM

KNURLED / HINGE RIGHT

KNURLED / HINGE LEFT

KNURLED / NO HINGE

1/4 TURN / HINGE TOP

1/4 TURN / HINGE BOTTOM

1/4 TURN / HINGE RIGHT

1/4 TURN / HINGE LEFT

1/4 TURN / NO HINGE

DIMENSIONS ARE SHOWN AS INCHES (MM)

NOTES :

S80P CONSTRUCTION IS ALL STEEL.
 STANDARD FINISH IS 44 BRITISH WHITE.

OPTIONAL ACCESSORIES :

- OBD (22 GA) STEEL OPPOSED BLADE DAMPER
- POBD (22 GA) STEEL OPPOSED BLADE DAMPER PAINTED FINISH
- 5OBD ALUMINUM OPPOSED BLADE DAMPER
- PLASTER FRAME

- 1" FILTER FRAME
- 2" FILTER FRAME
- SQUARE TO ROUND ADAPTER