

JOB NAME _____
 ARCHITECT _____
 ENGINEER _____
 CONTRACTOR _____
 LOCATION _____

SUBMITTALSHEET
 Form Number SG7024.1 Effective Date 5/13
 SG7024



1380P / 1380L Minimum Security Series Steel Supply / Return Grille Round / Square Perforated Pattern

1380-P
 SHOWN WITH OBD OPTION

1380-L

COUNTER SUNK SCREW HOLE OPTION

STRAIGHT SCREW HOLE OPTION

STANDARD FEATURES :

- 1380-P FACE PLATE :** 12 ga. steel with 5/16"(8) round holes on 7/16"(11) staggered centers.
- 1380-L FACE PLATE :** 12 ga. steel with 13/16" x 13/16" (21 x 21) square holes with 3/16"(5) frets.
- FINISH :** 44 British white
- SIZES** available in 2" (51) increments only.
 DUCT MIN 6" (152) x 4" (102)
 MAX 30" (762) x 30" (762)

OPTIONS : See screw hole chart for option details

- 3/16" (5) dia. straight screw holes.
- 3/16" (5) dia. counter sunk screw holes.
- Front operated opposed blade damper.
- 22 ga. steel plaster frame ships loose.
- 8PF plaster frame, see 8PF submittal

DIMENSIONS ARE SHOWN AS INCHES (MM).