B1 LOUVERED FACE DIFFUSERS



1450A, 51450A Series | 3-Cone, Adjustable



1450A

FEATURES


- Three cones for optimum airflow control.
- · Adjustable airflow pattern controller for vertical throw.
- · Great choice for variable air volume spaces.
- · Cones feature a one-piece stamped construction without mitered joints.
- · Round neck for easy connection to round duct.
- Anti-smudge design prevents smeared ceilings.
- · Two earthquake tabs are standard.

ACCESSORIES


- Optional round damper.
- Optional insulated backpan (24"x24" only).

1450A, 51450A Dimensional Information

1450A, 51450A, FACE VIEW



1450A, 51450A, CROSS SECTION



Introduction: 1450A Series •

The 1450A series are square face, 3-cone, round neck ceiling diffusers with adjustable airflow pattern controllers between the cones that change the discharge pattern from horizontal to vertical. They are available in a variety of frame styles to help meet the architectural requirements of today's ceilings. The spacing of the inner cones in relation to the backpan result in a design possessing anti-smudge characteristics, preventing the buildup of particles on the ceiling, which is achieved by minimizing the low pressure region inherent to most 4-way directional blow diffusers. The 1450A is typically used for spot heating or cooling applications in which airflow needs to be directed vertically in order to satisfy a specific load. It can also be applied as a seasonal air outlet device; adjusting for horizontal throw for cooling in warmer months and vertical throw for heating in colder months.

MODELS

1450A - Steel Louvered Diffuser 51450A - Aluminum Louvered Diffuser

PANEL SIZES

- 12"x12"
- 24"x24"

FINISHES

- Standard finish is #44 British White.
- Optional finishes available.

1450A, 51450A, 12"x12" PANEL DETAIL

Nominal Neck Size	Actual Neck Size	1450A	51450A
	A	В	В
06	5 7/8" (149)	1 1/4" (32)	1 1/4" (32)
08	7 7/8" (200)	1 1/4" (32)	1 1/4" (32)

1450A, 51450A, 24"x24" PANEL DETAIL

Nominal Neck Size	Actual Neck Size	1450A	51450A
	A	В	В
06	5 7/8" (149)	1 1/4" (32)	1 1/4" (32)
08	7 7/8" (200)	1 1/4" (32)	1 1/4" (32)
10	9 7/8" (251)	1 1/2" (38)	1 1/2" (38)
12	11 7/8" (302)	1 1/2" (38)	1 1/2" (38)
14	13 7/8" (352)	1 1/2" (38)	1 1/2" (38)
15	14 7/8" (378)	1 1/2" (38)	1 1/2" (38)

NOTE: Dimensions in parentheses are mm.

1 4 5

0 А

0 А