

**1900BOOT Suggested Specification & Configuration****1900BOOT**

The plenum for 1900 linear slot supply diffuser shall be Krueger model 1900BOOT and designed to attach to 1900 series with 1/2", 3/4", 1", 1 1/2", or 2" slot width. The 1900BOOT shall be constructed of galvanized steel with factory drawn inlet to prevent air leakage and fit 1, 2, 3, or 4 slot units.

Optional performance baffle is available to enhance the throw performance by shortening the throw and increasing the spread.

Optional internal insulation is available.

Optional quadrant damper for field attachment to the neck is available.

- 1. SERIES: (XXXXXXXX)**  
1900BOOT - Boot for Linear Slot Diffuser
- 2. LENGTH: (XX)**  
24", 36", 48", 60", or 72"
- 3. NUMBER OF SLOTS: (X) \***  
1, 2, 3, or 4
- 4. SLOT WIDTH: (XX)**  
50 - 1/2" Spacing  
75 - 3/4" Spacing  
10 - 1" Spacing  
15 - 1 1/2" Spacing  
20 - 2" Spacing
- 5. INLET SIZE: (XX)**  
6", 8", 10", or 12" Oval
- 6. FRAME STYLE: (X)**  
A - T-Bar Ceiling Mount  
B - Surface Mount with Screw Fastening  
C - Surface Mount with Concealed Fastening  
D - Plaster Tile Mount with Concealed Fastening  
E - Surface Mount with Sub-frame and Concealed Fastening  
F - "Discrete" Plaster Mount with Concealed Fastening  
I - Spline Ceiling  
J - Surface Mount with No Screw Holes  
K - Narrow-T Ceiling Mount
- 7. END BORDER: (X)**  
E - End Cap, Both Ends  
B - Butt Cut  
P - End Plate, Both Ends
- 8. DAMPER: (XX)**  
00 - No Damper  
21 - Quadrant Damper
- 9. ACCESSORIES: (XX) (XX)**  
00 - No Accessories  
G - Baffle  
H - Insulation
- 10. FINISH: (XX)**  
01 - Mill

\* Contact Krueger for slot numbers greater than four slots.

**SAMPLE CONFIGURATION:** 1900BOOT - 48 - 3 - 10 - 10 - C - E - 00 - H - 00 - 01