

## Product Weights

| Single Duct Terminal Units |                     |             |                  |                  |                |       |
|----------------------------|---------------------|-------------|------------------|------------------|----------------|-------|
| LMHS                       | Unit Weights (lbs.) |             |                  |                  | Hot Water Coil |       |
| Size                       | Bare Box            | w/pneumatic | w/ DDC or Analog | w/ Attenuator    | 1 Row          | 2 row |
| 4,5,6                      | 14                  | +4          | +9               | +10              | +5             | +6    |
| 7,8                        | 16                  | +4          | +9               | +12              | +5             | +7    |
| 9,10                       | 21                  | +4          | +9               | +16              | +7             | +9    |
| 12                         | 26                  | +4          | +9               | +21              | +9             | +12   |
| 14                         | 34                  | +4          | +9               | +24              | +10            | +15   |
| 16                         | 38                  | +4          | +9               | +27              | +12            | +17   |
| 22                         | 65                  | +4          | +9               | +30              | +17            | +25   |
| LMHS-LC                    | Unit Weights (lbs.) |             |                  |                  | Hot Water Coil |       |
| Size                       | Bare Box            | w/pneumatic | w/ DDC or Analog | w/ Attenuator    | 1 Row          | 2 row |
| 4,5,6                      | 16                  | +4          | +9               | +12              | +5             | +7    |
| 7,8                        | 21                  | +4          | +9               | +16              | +7             | +9    |
| 9,10                       | 26                  | +4          | +9               | +21              | +9             | +12   |
| 12                         | 34                  | +4          | +9               | +24              | +10            | +15   |
| 14                         | 38                  | +4          | +9               | +27              | +12            | +17   |
| Fan Powered Terminal Units |                     |             |                  |                  |                |       |
| QFC                        | Unit Weights (lbs.) |             |                  |                  | Hot Water Coil |       |
| Size                       | Bare Box            | w/pneumatic | w/ DDC or Analog | w/ Electric Heat | 1 Row          | 2 Row |
| 2                          | 70                  | +4          | +9               | +30              | +19            | +21   |
| 3                          | 70                  | +4          | +9               | +30              | +20            | +22   |
| 4                          | 85                  | +4          | +9               | +32              | +22            | +25   |
| 5                          | 85                  | +4          | +9               | +32              | +24            | +28   |
| 6                          | 100                 | +4          | +9               | +35              | +25            | +30   |
| 7                          | 175                 | +4          | +9               | +40              | +35            | +43   |
| QFV                        | Unit Weights (lbs.) |             |                  |                  | Hot Water Coil |       |
| Size                       | Bare Box            | w/pneumatic | w/ DDC or Analog | w/ Electric Heat | 1 Row          | 2Row  |
| 2                          | 114                 | +4          | +9               | +30              | +19            | +21   |
| 3                          | 114                 | +4          | +9               | +30              | +20            | +22   |
| 4                          | 115                 | +4          | +9               | +32              | +22            | +25   |
| 5                          | 122                 | +4          | +9               | +32              | +24            | +28   |
| 6                          | 123                 | +4          | +9               | +35              | +25            | +30   |
| 7                          | 127                 | +4          | +9               | +40              | +35            | +43   |
| KQFP                       | Unit Weights (lbs.) |             |                  |                  | Hot Water Coil |       |
| Size                       | Bare Box            | w/pneumatic | w/ DDC or Analog | w/ Electric Heat | 1 Row          | 2 Row |
| 2                          | 185                 | +4          | +9               | +30              | +9             | +12   |
| 3                          | 200                 | +4          | +9               | +30              | +9             | +12   |
| 4                          | 200                 | +4          | +9               | +32              | +9             | +12   |
| 5                          | 225                 | +4          | +9               | +32              | +12            | +17   |
| 6                          | 250                 | +4          | +9               | +35              | +12            | +17   |
| 7                          | 260                 | +4          | +9               | +40              | +12            | +17   |

## Product Weights

### Fan Powered Terminal Units, cont...

| KFSS Unit Weights (lbs.) |          |                    |               |       |       |       |                |                                |                           |                              |                              |
|--------------------------|----------|--------------------|---------------|-------|-------|-------|----------------|--------------------------------|---------------------------|------------------------------|------------------------------|
| Unit Size                | Bare Box | With Electric Heat | Hot Water Add |       |       |       | Attenuator Add | Standard Control Enclosure Add | 90° Control Enclosure Add | Bottom Control Enclosure Add | Remote Control Enclosure Add |
|                          |          |                    | 1-Row         | 2-Row | 3-Row | 4-Row |                |                                |                           |                              |                              |
| 3                        | 80       | 21                 | 9             | 11    | 15    | 19    | 7              | 11                             | 27                        | 21                           | 18                           |
| 4                        | 90       | 21                 | 12            | 17    | 23    | 28    | 7              | 11                             | 27                        | 21                           | 18                           |
| 5                        | 110      | 21                 | 12            | 17    | 23    | 28    | 9              | 11                             | 27                        | 21                           | 18                           |
| 6                        | 120      | 24                 | 12            | 17    | 23    | 28    | 10             | 11                             | 27                        | 21                           | 18                           |
| 7                        | 165      | 39                 | 20            | 29    | 39    | 48    | 20             | 11                             | 27                        | 21                           | 18                           |

### Low Profile Fan Powered Terminal Units

| Low Profile Fan Powered Terminal Units |          |                     |                  |                  |                |       |
|----------------------------------------|----------|---------------------|------------------|------------------|----------------|-------|
| KLPS                                   |          | Unit Weights (lbs.) |                  |                  | Hot Water Coil |       |
| Size                                   | Bare Box | w/pneumatic         | w/ DDC or Analog | w/ Electric Heat | 1 Row          | 2 Row |
| 1                                      | 80       | N/A                 | +9               | +25              | +8             | +10   |
| 2                                      | 85       | N/A                 | +9               | +30              | +8             | +10   |
| 3                                      | 90       | +4                  | +9               | +30              | +10            | +12   |
| 4                                      | 110      | +4                  | +9               | +35              | +12            | +14   |
| 5                                      | 120      | +4                  | +9               | +35              | +12            | +14   |
|                                        |          |                     |                  |                  |                |       |
| KLPP                                   |          | Unit Weights (lbs.) |                  |                  | Hot Water Coil |       |
| Size                                   | Bare Box | w/pneumatic         | w/ DDC or Analog | w/ Electric Heat | 1 Row          | 2 Row |
| 2                                      | 91       | +4                  | +9               | +25              | +9             | +12   |
| 4                                      | 106      | +4                  | +9               | +25              | +9             | +12   |

### DOAS Fan Powered Terminal Units

| KLPS-D |          | Unit Weights (lbs.) |                  |                  | Hot Water Coil |       | Cooling Coil |       |       |
|--------|----------|---------------------|------------------|------------------|----------------|-------|--------------|-------|-------|
| Size   | Bare Box | w/pneumatic         | w/ DDC or Analog | w/ Electric Heat | 1 Row          | 2 Row | 2 Row        | 4 Row | 6 Row |
| 1      | 80       | +4                  | +9               | +25              | +8             | +10   | +20          | +30   | +40   |
| 2      | 85       | +4                  | +9               | +25              | +8             | +10   | +20          | +30   | +40   |
| 3      | 90       | +4                  | +9               | +30              | +10            | +12   | +25          | +35   | +45   |
| 5      | 120      | +4                  | +9               | +35              | +12            | +14   | +30          | +40   | +50   |

## Product Weights

| <b>Dual Duct Terminal Units</b> |                            |                    |                         |
|---------------------------------|----------------------------|--------------------|-------------------------|
| <b>LMHD</b>                     | <b>Unit Weights (lbs.)</b> |                    |                         |
| <b>Size</b>                     | <b>Bare Box</b>            | <b>w/pneumatic</b> | <b>w/ DDC or Analog</b> |
| 4,5,6                           | 29                         | +8                 | +18                     |
| 7,8                             | 33                         | +8                 | +18                     |
| 9,10                            | 41                         | +8                 | +18                     |
| 12                              | 51                         | +8                 | +18                     |
| 14                              | 67                         | +8                 | +18                     |
| 16                              | 75                         | +8                 | +18                     |
| 22                              | 129                        | +8                 | +18                     |
|                                 |                            |                    |                         |
| <b>LMHDT</b>                    | <b>Unit Weights (lbs.)</b> |                    |                         |
| <b>Size</b>                     | <b>Bare Box</b>            | <b>w/pneumatic</b> | <b>w/ DDC or Analog</b> |
| 6                               | 31                         | +8                 | +18                     |
| 8                               | 42                         | +8                 | +18                     |
| 10                              | 61                         | +8                 | +18                     |
| 12                              | 80                         | +8                 | +18                     |
| 14                              | 98                         | +8                 | +18                     |
| 16                              | 111                        | +8                 | +18                     |

| <b>Retrofit Terminal Units</b> |                            |                     |                         |
|--------------------------------|----------------------------|---------------------|-------------------------|
| <b>RVE</b>                     | <b>Unit Weights (lbs.)</b> |                     |                         |
| <b>Size</b>                    | <b>Bare Box</b>            | <b>w/pneumatic</b>  | <b>w/ DDC or Analog</b> |
| 4,5,6                          | 12                         | +4                  | +9                      |
| 7,8                            | 14                         | +4                  | +9                      |
| 9,10                           | 19                         | +4                  | +9                      |
| 12                             | 24                         | +4                  | +9                      |
| 14                             | 32                         | +4                  | +9                      |
| 16                             | 36                         | +4                  | +9                      |
|                                |                            |                     |                         |
| <b>SVE Size</b>                | <b>Damper Size</b>         | <b>Weight (lbs)</b> |                         |
| A                              | 5in x 5in                  | 5                   |                         |
| B                              | 6in x 6in                  | 7                   |                         |
| C                              | 8in x 6in                  | 8                   |                         |
| D                              | 10in x 8in                 | 12                  |                         |
| E                              | 14in x 8in                 | 16                  |                         |
| F                              | 18in x 6in                 | 16                  |                         |
| G                              | 12in x 10in                | 17                  |                         |
| H                              | 18in x 10in                | 25                  |                         |
| J                              | 18in x 12in                | 29                  |                         |
| K                              | 20in x 14in                | 37                  |                         |
| L                              | 30in x 12in                | 47                  |                         |
| M                              | 22in x 16in                | 46                  |                         |
| N                              | 24in x 18in                | 56                  |                         |
| P                              | 30in x 20in                | 77                  |                         |
| R                              | 40in x 20in                | 102                 |                         |

# Product Weights

| Bypass Terminal Units |                     |                         |
|-----------------------|---------------------|-------------------------|
| KLB                   | Unit Weights (lbs.) |                         |
| Size                  | Bare Box            | w/pneumatic or electric |
| 6                     | 19                  | +4                      |
| 8                     | 19                  | +4                      |
| 10                    | 21                  | +4                      |
| 12                    | 27                  | +4                      |
| 14                    | 27                  | +4                      |
| 16                    | 34                  | +4                      |
| 18                    | 34                  | +4                      |