



KSB, KSL - VERTICAL DOWNSIZED BLOWER COIL STANDARD DISCHARGE SECTION


JOB NAME **ENGINEER** CONTRACTOR TAG

SUBMITTAL SHEET



TOP VIEW





SIZE	Н	W	L	Α	В
08	12	26	19	15	20
	[305]	[660]	[483]	[381]	[508]
12	12	26	21	17	20
	[305]	[660]	[533]	[432]	[508]
16	14	29	25	21	23
	[356]	[737]	[635]	[533]	[584]
20	14	29	28	24	23
	[356]	[737]	[711]	[610]	[584]
25	18	39	28	24	33
	[457]	[991]	[711]	[610]	[838]
30	18	39	28	24	33
	[457]	[991]	[711]	[610]	[838]

NOTES:

- ALL DIMENSIONS ARE INCHES [MM]

- ALL DIMENSIONS ARE ±1/4" [6]
 METRIC VALUES ARE SOFT CONVERSION
 COIL PIPING NOT SHOWN FOR CLARITY; SEE COIL CONNECTION DRAWINGS FOR DETAILS
 STEAM HEATING COILS MUST BE MOUNTED IN DISCHARGE SECTION
- DISCHARGE SECTION MAY NOT BE COMBINED WITH BLOW-THRU ELECTRIC HEAT

NEW Revision Date: 12/14 BCS18-SDC01 Replaces: Form: