



SIZE	A	C	D	E
20	20 [508]	21 [533]	22 [559]	30 [762]
25	26 [660]	27 [686]	28 [711]	36 [914]
30	30 [762]	31 [787]	32 [813]	40 [1016]
40	40 [1016]	41 [1041]	42 [1067]	50 [1270]
50	50 [1270]	51 [1295]	52 [1321]	60 [1524]
60	60 [1524]	61 [1549]	62 [1575]	70 [1778]

- NOTES:
- ALL DIMENSIONS ARE INCHES [MM]
 - ALL DIMENSIONS ARE $\pm 1/4"$ [6]
 - METRIC VALUES ARE SOFT CONVERSION
 - LEFT HAND UNIT SHOWN, RIGHT HAND UNIT OPPOSITE
 - STANDARD BOTTOM CONTROL ENCLOSURE WITH HINGED COVER
 - INCLUDES (2) KNOCKOUTS ON EACH SIDE OF UNIT CASING AND (2) ADDITIONAL KNOCKOUTS ON BOTTOM OF UNIT, ON LEFT SIDE
 - PROVIDE SUFFICIENT CLEARANCE TO ACCESS ELECTRICAL CONTROLS AND COMPLY WITH APPLICABLE CODES AND ORDINANCES
 - STANDARD EXTERNALLY FOAM COATED GALVANIZED STEEL DRAIN PAN HAS 7/8" ODM COPPER OUTLET
 - STAINLESS STEEL DRAIN PAN HAS 3/4" MPT GALVANIZED STEEL OUTLET
 - AUX. DRAIN OUTLET IS 5/8" ODM COPPER OR 3/8" MPT GALVANIZED STEEL RESPECTIVELY
 - SEE COIL CONNECTION DRAWINGS FOR COIL CONNECTION SIZES AND LOCATIONS

Revision Date: 04/15

Form: FCS01-KHFH02

Replaces: NEW