



SIZE	A	C	D	E
20	20 [508]	21 [533]	22 [559]	19-1/2 [495]
25	26 [660]	27 [686]	28 [711]	19-1/2 [495]
30	30 [762]	31 [787]	32 [813]	19-1/2 [495]
40	40 [1016]	41 [1041]	42 [1067]	19-1/2 [495]
50	50 [1270]	51 [1295]	52 [1321]	19-1/2 [495]
60	60 [1524]	61 [1549]	62 [1575]	19-1/2 [495]

- NOTES:
- ALL DIMENSIONS ARE INCHES [MM]
  - ALL DIMENSIONS ARE  $\pm 1/4"$  [6]
  - METRIC VALUES ARE SOFT CONVERSION
  - LEFT HAND UNIT SHOWN, RIGHT HAND UNIT OPPOSITE
  - STANDARD CONTROL ENCLOSURE IS MOUNTED ON UNIT SIDE OPPOSITE COOLING COIL INSTRUCTIONS
  - UNIT CASING INCLUDES (2) KNOCKOUTS ON EACH SIDE.
  - PROVIDE SUFFICIENT CLEARANCE TO ACCESS ELECTRICAL CONTROLS AND COMPLY WITH APPLICABLE CODES AND ORDINANCES
  - OPTIONAL BOTTOM CONTROL ENCLOSURE WITH HINGED COVER REPLACES STANDARD SIDE MOUNTED ENCLOSURE
  - INCLUDES (2) ADDITIONAL KNOCKOUTS ON BOTTOM OF UNIT, ON LEFT SIDE
  - SEE COIL CONNECTION DRAWINGS FOR COIL CONNECTION SIZES AND LOCATIONS

Revision Date: 04/15

Form: FCS01-KHFH03

Replaces: NEW