



SIZE	A	C	D	E	F
20	20 [508]	21 [533]	22 [559]	19 [483]	28-3/8 [721]
25	26 [660]	27 [686]	28 [711]	25 [635]	28-3/8 [721]
30	30 [762]	31 [787]	32 [813]	29 [737]	28-3/8 [721]
40	40 [1016]	41 [1041]	42 [1067]	39 [991]	28-3/8 [721]
50	50 [1270]	51 [1295]	52 [1321]	49 [1245]	28-3/8 [721]
60	60 [1524]	61 [1549]	62 [1575]	59 [1499]	28-3/8 [721]

- NOTES:**
- ALL DIMENSIONS ARE INCHES [MM]
 - ALL DIMENSIONS ARE ±1/4" [6]
 - METRIC VALUES ARE SOFT CONVERSION
 - LEFT HAND UNIT SHOWN, RIGHT HAND UNIT OPPOSITE
 - STANDARD CONTROL ENCLOSURE IS MOUNTED ON UNIT SIDE OPPOSITE COOLING COIL CONNECTIONS.
 - UNIT CASING INCLUDES (2) KNOCKOUTS ON EACH SIDE.
 - PROVIDE SUFFICIENT CLEARANCE TO ACCESS ELECTRICAL CONTROLS AND COMPLY WITH APPLICABLE CODES AND ORDINANCES
 - OPTIONAL BOTTOM CONTROL ENCLOSURE WITH HINGED COVER REPLACES STANDARD SIDE MOUNTED ENCLOSURE
 - INCLUDES (2) ADDITIONAL KNOCKOUTS ON BOTTOM OF UNIT, ON LEFT SIDE
 - SEE COIL CONNECTION DRAWINGS FOR COIL CONNECTION SIZES AND LOCATIONS

Revision Date: 06/19	Form: FCS01-KHFP03-02	Replaces: FCS01-KHFP03-01
----------------------	-----------------------	---------------------------