



SIZE	A	C	D	E	F
20	20 [508]	21 [533]	22 [559]	19 [483]	30 [762]
25	26 [660]	27 [686]	28 [711]	25 [635]	36 [914]
30	30 [762]	31 [787]	32 [813]	29 [737]	40 [1016]
40	40 [1016]	41 [1041]	42 [1067]	39 [991]	50 [1270]
50	50 [1270]	51 [1295]	52 [1321]	49 [1245]	60 [1524]
60	60 [1524]	61 [1549]	62 [1575]	59 [1499]	70 [1778]

- NOTES:
- ALL DIMENSIONS ARE INCHES [MM]
 - ALL DIMENSIONS ARE ±1/4" [6]
 - METRIC VALUES ARE SOFT CONVERSION
 - LEFT HAND UNIT SHOWN, RIGHT HAND UNIT OPPOSITE
 - STANDARD CONTROL ENCLOSURE IS MOUNTED ON UNIT SIDE OPPOSITE COOLING COIL CONNECTIONS
 - UNIT CASING INCLUDES (2) KNOCKOUTS ON EACH SIDE
 - PROVIDE SUFFICIENT CLEARANCE TO ACCESS ELECTRICAL CONTROLS AND COMPLY WITH APPLICABLE CODES AND ORDINANCES
 - OPTIONAL BOTTOM CONTROL ENCLOSURE WITH HINGED COVER REPLACES STANDARD SIDE MOUNTED ENCLOSURE
 - INCLUDES (2) ADDITIONAL KNOCKOUTS ON BOTTOM OF UNIT, ON LEFT SIDE
 - STANDARD EXTERNALLY FOAM COATED GALVANIZED STEEL DRAIN PAN HAS 7/8" ODM COPPER OUTLET
 - STAINLESS STEEL DRAIN PAN HAS 3/4" MPT GALVANIZED STEEL OUTLET
 - AUX. DRAIN OUTLET IS 5/8" ODM COPPER OR 3/8" MPT GALVANIZED STEEL RESPECTIVELY
 - SEE COIL CONNECTION DRAWINGS FOR COIL CONNECTION SIZES AND LOCATIONS
 - 6" [152] ROUND O.A. INLET IS UNFILTERED
 - OPTIONAL REDUCER FOR APPLICATIONS WITH A 4" [102] ROUND O.A. REQUIREMENT

Revision Date: 06/19

Form: FCS01-KHFP06-02

Replaces: FCS01-KHFP06-01