


☐ **FRAME 23  
LAY-IN T-BAR**

☐ **FRAME 98  
NARROW-T**

**STANDARD FEATURES:**

- Variable air volume diffuser for stand-alone operation
- Square, plaque faced, architectural diffuser with neck mounted modulating damper
- Full 360°, horizontal discharge pattern remains tight over a wide range of airflows
- Factory mounted actuator, controller, and discharge temperature sensor
- Field installed, digital, non-programmable thermostat is required on primary units
- Control up to 20 different diffusers from one thermostat
- Automatic change over control for both heating and cooling applications
- All electronic components are low voltage
- Steel construction
- Standard finish is 44-British White

**OPTIONAL FEATURES:**

- Control Mode
  - ☐ Primary (Requires Thermostat)
  - ☐ Secondary
- Transformers
  - ☐ 40 VA – 120V, Up to 12 Diffusers
  - ☐ 75 VA – 120V/208V/240V, Up to 24 Diffusers
  - ☐ 100 VA – 120V/240V/277V, Up to 35 Diffusers
  - ☐ 40 VA – Transformer Mounted in a 4x4 Box
- Options
  - ☐ Wall Mounted Digital Thermostat
  - ☐ Wall Mounting Backplate for Thermostat
  - ☐ Wall Mounted BACnet Thermostat
- Available Sizes

Panel	Neck	A	B
12x12	6, 8	1 1/8	9
24x24	6, 8, 10, 12, 14	2 1/2	18

**RELATED SUBMITTALS**

- DS0823 (DIGITAL THERMOSTAT)